



Lubrita DEO HDX 20W-20

An universal engine oil

ST-CVL-4051

Heavy duty diesel engine oils

Product Description and Benefits

An universal engine oil produced with high quality solvent refined base oils and a well-balanced choice of additives. This engine oil has the following properties:

- an excellent detergency preventing from deposits in the hot zones of the engine
- a very active dispersion, that prevents from precipitation and sludge
- a powerful action against wear, corrosion and foam
- low ash contents

Application

This universal lubricating oil is suitable for gasoline and diesel engines, with or without supercharging, under all operating conditions.

Lubrita DEO HDX 20W-20 meets the following performance specifications:

API SG/CF

ACEA E2

Meets the requirements of

MB 227.0/228.0

MAN 270

Typical Analysis

Property	Unit	Typical Value
Density @15°C	kg/	0,879
Viscosity -15 °C	mPa.s	5200
Viscosity 40 °C	mm ² /s	54,60
Viscosity 100 °C	mm ² /s	8,09
Viscosity Index		117
Flash Point COC	°C	215
Pour Point	°C	-25
Total Base Number	mgKOH/g	7,1
Sulphate Ash	%	0,91

Health and Safety

Based on available information, this product is not expected to produce adverse effects on health when used for the intended application and the recommendations provided in the Material Safety Data Sheet (MSDS) are followed. MSDS's are available upon request through your sales contract office, or via the Internet. This product should not be used for purposes other than its intended use. If disposing of used product, take care to protect the environment. Lubrita check oil level design is trade mark of PMM Ltd. or one of it's subsidiaries.

More information available:

web page: www.lubrita.com
e-mail: info@lubrita.com