



## Lubrigrease C 3

**GRS-6026**

*Special application grease*

### CLASSIFICATION

DIN 51502 K3C-25  
ISO 6743 ISO-L-XBAAA3

### PRODUCT DESCRIPTION

Lubrigrease C 3 is a hydrated calcium thickened lubricating grease based on mineral oil. The grease also contains antioxidants.

The thickener makes the product highly water resistant. Together with the stiff consistency the grease acts as a seal as well as a lubricant.

Lubrigrease C 3 is a high quality grease suitable for lubrication of marine applications and in various wet environments.

- Good mechanical stability
- Excellent sea and fresh water resistance

### TYPICAL TECHNICAL DATA

Thickener		Calcium, hydrated
Base oil		Mineral oil
Colour	Visual	Beige
NLGI Grade	ASTM D217	3
Dropping point	IP 396	>90°C
Base oil viscosity at 40°C	ISO 12058	110 mm <sup>2</sup> /s
Base oil viscosity at 100°C	ISO 12058	12 mm <sup>2</sup> /s
Temperature range		-25°C to +60°C Max +80°C

### Health and Safety

Based on available information, this product is not expected to produce adverse effects on health when used for the intended application and the recommendations provided in the Material Safety Data Sheet (MSDS) are followed. MSDS's are available upon request through your sales contract office, or via the Internet. This product should not be used for purposes other than its intended use. If disposing of used product, take care to protect the environment. Lubrita check oil level design is trade mark of PMM Ltd. or one of its subsidiaries.

More information available:

web page: [www.lubrita.com](http://www.lubrita.com)  
e-mail: [info@lubrita.com](mailto:info@lubrita.com)



## TYPICAL TECHNICAL DATA

### Mechanical stability

Penetration 60 strokes

ISO 2137

### Typical Value

220-250

Penetration 100.000 strokes

ISO 2137

+35

### Water stability

Water resistance

DIN 51807/1

1-90

Water washout 1h/80°C

ISO 11009

2%

### Oil Separation

Separation 168h/40°C

IP 121

1%

## Health and Safety

Based on available information, this product is not expected to produce adverse effects on health when used for the intended application and the recommendations provided in the Material Safety Data Sheet (MSDS) are followed. MSDS's are available upon request through your sales contract office, or via the Internet. This product should not be used for purposes other than its intended use. If disposing of used product, take care to protect the environment. Lubrita check oil level design is trade mark of PMM Ltd. or one of it's subsidiaries.

More information available:

web page: [www.lubrita.com](http://www.lubrita.com)  
e-mail: [info@lubrita.com](mailto:info@lubrita.com)